



Product Information

TVM24128

Touch Vision LCD Module

Description:

The TVM24128 Touch Vision Module provides a complete user interface in a low cost, convenient to use module. It combines either a transreflective or transmissive graphics LCD display, touch activated panel overlay, interface electronics, LCD drivers, EL back light, and power supply voltage converters. Because the TVM24128 contains on board voltage converters, only a single +5 Volt power supply is required.

The TVM24128 includes a powerful micro-processor which acts as an intelligent controller for the entire module thus making interfacing to the TVM24128 very easy. Communication with the TVM24128 is done via either a 20 wire parallel port, 8 bit instruction and data, or an RS232 serial port. Hand shaking signals are provided to control data flow and a status register is also provided to better accommodate pipe lined communication.

A rich instruction set, including both text and graphics commands, is provided. With these commands, the user can freely mix and manipulate any graphics and text being displayed. Commands can be issued to position the cursor, set up the text window size and set system attributes. Graphics commands are provided to draw rectangles, boxes, lines, vectors or to set individual pixels. Two graphics planes are provided to accommodate background and foreground operations. Four level gray scale is also an integral part of the instruction set.

Additional commands are available to activate a touch panel switch area as well as place a button outline on the LCD display automatically. The host can load the TVM24128 with the button label and then place the button via a single instruction. If enabled, the software automatically sizes the button, places the text in the center of the button, writes the button to the display, and then activates the touch panel in the button's location. When the button is pressed, the on board CPU signals the host that a button has been actuated and makes the button's code available for reading by the host. Other button commands may be used to activate a "phantom button" area, delete a button, or delete all buttons.

The TVM24128 has the ability to simultaneously mix as many as 5 fonts on the screen. Two fonts are resident in the TVM24128 controller. Up to three fonts can be custom

designed and compiled using the font compiler which is part of the designer's kit. These custom fonts can be down loaded into the TVM24128's font memory and the used. Any font may be used at any time for labels anywhere, including text inside a defined button area.

Electronic contrast control eliminates the need for any hardware contrast adjustments by end users of the equipment. In addition, a course adjustment trimmer is provided on the controller board to accommodate initial factory settings. Full temperature range compensation controls variations due to the environment.

An EL back-light (including high voltage driver) is included on the TVM24128. The back light can be turned ON and OFF via an on board switch by issuing a command to the TVM24128.

Features:


- 240 X 128 Super Twist LCD Display
- Transmissive or Transreflective Versions
- 6 X 10 Matrix Touch Panel Overlay
- Single +5 Volt Power Supply Operation
- 4 Level Gray Scale Capability
- Software Controlled Long Life EL Back Light
- Compact Size
- Software Controlled Electronic Contrast
- 2 Built in Fonts
- Up to 3 Down Loaded Soft Fonts
- Audio Alarm and or Key Click
- 4 Programmable Auxiliary Digital Outputs
- 8 Auxiliary Digital Inputs
- Automatic Scrolling in Text Window
- Freely Mixed Multiple Font Types
- Auto Button Generation and Placement
- An Abundance of Graphics Commands
- 8 Bit Parallel and RS232 Serial Interfaces

TVM24128

Display and Touch Panel Layout

The LCD display is organized in an array 240 dots wide by 128 dots tall. The upper left hand corner of the display is always 0,0 (X,Y). The lower right is 239,127. All coordinates, whether for cursor placement or for placements of graphics use the same coordinate entry methodology and are always referenced to the upper left corner of the display.

The touch panel is organized as an array, 10 wide by 6 tall, of touch sensitive cells. The upper left hand cell is referred to as 0,0 and the lower right cell is 9,5. Each cell is 20 pixels wide by 18 pixels high. A horizontal space 4 pixels wide and a vertical space of 3 pixels is left as an easement between each touch panel cell.



Touch Panel Overlay Detail

TVM24128

Parallel System Interface

Connecting the TVM24128 to the host micro-processor is done via a 20 pin ribbon cable which is connected to JF1 at the bottom of the module. Power and ground are provided to the module through this cable when using the parallel interface. The TVM24128 uses an 8 bit instruction/data bus as well as 2 address lines. There are also several control signals and status lines.

| Pin # | Function | Description | Type |
|-------|----------|------------------------------|-------|
| 1 | VSS | VSS Power connection | Power |
| 2 | RESET/ | Module Reset, Negative | Out |
| 3 | DEN/ | Module Enable, Negative | In |
| 4 | DRD/ | Read, Negative | In |
| 5 | DWR/ | Write, Negative | In |
| 6 | DIBF | Input Buffer Full, Positive | Out |
| 7 | DOBF/ | Output Buffer Full, Negative | Out |
| 8 | ERROR | Module Error, Positive | Out |
| 9 | KEYPRESS | Key Pressed Flag, Positive | Out |
| 10 | DA0 | Address 0 | In |
| 11 | DA1 | Address 1 | In |
| 12 | D0 | Data 0 | I/O |
| 13 | D1 | Data 1 | I/O |
| 14 | D2 | Data 2 | I/O |
| 15 | D3 | Data 3 | I/O |
| 16 | D4 | Data 4 | I/O |
| 17 | D5 | Data 5 | I/O |
| 18 | D6 | Data 6 | I/O |
| 19 | D7 | Data 7 | I/O |
| 20 | VCC | Power | Power |

JF1 Connections

Instructions for the TVM24128 are always written to address 0. If the instruction requires additional data, the data is written to address 1. This is done to facilitate data strings of arbitrary length such as text input or down loading of fonts. String data is always terminated by writing the next instruction to address 0. Instructions having data of an arbitrary amount are referred to as having "String" data.

Any instruction requiring more data before it can execute may be aborted by writing the next instruction to the instruction register.

Some instructions will return data which is always read at address 0. The status register may be read at any time from address 3. The table below summarizes the address mapping.

| DA1 | DA0 | Write | Read |
|-----|-----|-------------|--------|
| 0 | 0 | Instruction | Data |
| 0 | 1 | Data | |
| 1 | 0 | | |
| 1 | 1 | | Status |

Address Mapping

TVM24128


Signal Descriptions

| DEN/ | DWR/ | DRD/ | DA0 | DA1 | Action |
|------|------|------|-----|-----|----------------------|
| 1 | x | x | x | x | No Action |
| 0 | 1 | 1 | x | x | No Action |
| 0 | 0 | 1 | 0 | 0 | Write Instruction |
| 0 | 0 | 1 | 1 | 0 | Write Data |
| 0 | 0 | 1 | 0 | 1 | Illegal |
| 0 | 0 | 1 | 1 | 1 | Illegal |
| 0 | 1 | 0 | 0 | 0 | Read Data |
| 0 | 1 | 0 | 1 | 0 | Illegal |
| 0 | 1 | 0 | 0 | 1 | Illegal |
| 0 | 1 | 0 | 1 | 1 | Read Status Register |

Interface Signals

RESET/

A logic 0 level on this pin causes a reset of the module. If this pin is left open, the internal RC reset network on the module will cause a reset. It should be noted that the internal capacitor in the TVM24128 will hold down the RESET/ line and any external circuitry tied to the this pin. It is important that sufficient time be allocated to allow the TVM24128 to complete reset and start up prior to receiving instructions from the host processor.



Reset Circuit Diagram

DEN/, DRD/, DWR/

A logic 0 level on DEN/ and DWR/ will cause a write to the TVM24128. A logic 0 level on DEN/ and DRD/ will cause a read from the TVM24128. Please refer to page 4 for DA0 and DA1 addressing information.

DIBF (Input Buffer Full)

The TVM24128 uses an 8255 PPI device to act as an I/O buffer to the controller. Instruction and data information is always written to this buffer. The I/O buffer can hold information for the next instruction while the controller processes the current instruction so there is one level of pipe lining of data to the module. This is an important point to remember when interfacing the module. DIBF provides a signal to indicate if the TVM24128 can accept data. A logic 0 indicates that the TVM24128 is ready for the next instruction or data. A logic 1 indicates that the input buffer to the controller is full and the module is busy. Therefore, the DIBF signal does not indicate that the controller has completed execution of the current instruction, it only indicates that the input buffer is empty and that new information may be written. DIBF can also be read through the status register.

DOBF/ (Output Buffer Full)

A logic 0 on DOBF/ indicates that the controller has placed data into the I/O buffer to be read by the external micro-processor. As soon as the data is read, the DOBF/ line returns to a logic 1. DOBF/ can also be read through the status register. DOBF/ will stay set until the data is read from the TVM24128 or until the reset line is pulled low. i.e. if a user program requests information, but never takes this information, the DOBF/ flag will remain set. When the next request for information is made,

the main program will detect the DOBF/ flag set and immediately retrieve the previous instruction's information. To avoid this problem, be sure to always read the output register when the DOBF/ flag is set .

ERROR

Because of the intelligent nature of the TVM24128, some instructions may cause an error if they can not be executed. One cause may be providing the instruction with data that produces an internal error. An example would be trying to place a button on top of another button. The second button would not be placed and the ERROR flag would be set to a logic 1. It will stay set until the next instruction is executed. The ERROR flag has different meanings depending on the instruction being executed. Please refer to Section 2 for the specific ERROR flag meaning for each instruction. ERROR can also be read through the status register.

KEYPRESS

The KEYPRESS flag indicates that a button has been pressed and that the external micro-processor may now read the "Button Code". This code indicates which button has been pressed. The "Button Code" is assigned to a button when it is placed on the display. More information can be found in section 3.6.1 of the Designer's Manual. KEYPRESS can also be read through the status register.

DA0, DA1

DA0 and DA1 are used to address the different module registers. Please refer to the table on page 4 for more information.

D0 - D7

D0 through D7 forms the 8 bit bi-directional data buss to the module.

Status Register

In some applications you may prefer to read a status register rather than use "hardware hand shaking". A status register is provided on the TVM24128 which stores the "hand shaking" signals previously described. The status register can be read at address 3 at any time without affecting the writing or reading of instructions or data. See the table below for more information.

The status register has a signal, CPUBUSY, that can be used to indicate whether or not the CPU is executing the current instruction. This flag is set high when an instruction is loaded into the instruction register (address 0) and stays set high until the instruction is completed.

| Bit | Function |
|--------|----------|
| 0(LSB) | DIBF |
| 1 | DOBF/ |
| 2 | ERROR |
| 3 | KEYPRESS |
| 4 | CPUBUSY |
| 5 | 0 |
| 6 | 0 |
| 7(MSB) | 0 |

Status Register Bit Functions

TVM24128

Auxiliary Control Port

The auxiliary control port, labeled JD1 on the back view of the TVM24128, enables access to 4 open collector NPN outputs and 8 CMOS digital inputs via the Write Aux Port and Read Aux Port instructions. The inputs are normally pulled up to Vcc through 22K Ohm resistors. The pin functions of JD1 are listed below. A logic one sent to an output turns the appropriate open collector transistor on to pull to ground.

| Pin Number | Description | Pin Type |
|------------|-------------|----------|
| 1 | Vss | Power |
| 2 | Aux In 7 | Input |
| 3 | Aux In 6 | Input |
| 4 | Aux In 5 | Input |
| 5 | Aux In 4 | Input |
| 6 | Aux In 3 | Input |
| 7 | Aux In 2 | Input |
| 8 | Aux In 1 | Input |
| 9 | Aux In 0 | Input |
| 10 | Aux Out 3 | Output |
| 11 | Aux Out 2 | Output |
| 12 | Aux Out 1 | Output |
| 13 | Aux Out 0 | Output |
| 14 | Vcc | Power |

JD1 Auxiliary Port Connections

RS232 Serial Interface

In addition to a parallel interface, the TVM24128 includes an RS232 interface which uses a programming language called TVSGL (Touch Vision Serial Graphics Language). With only a few exceptions, all commands and data are given as simple ASCII strings, similar to those produced by a terminal. As an example, to move the cursor to a new position using the parallel interface you would issue the SetXY command plus give the position in binary code to the input port. Using TVSGL, the command would be the simple ASCII string CS50,100 which would position the cursor at the 50/100 display co-ordinate.

Special characters, described in detail later, are used to control the hand shaking protocol and status information.

Basic Command Structure

Serial commands are two characters long. After a serial command is issued, data is provided by giving the ASCII string equivalent of the numeric value required. Data values are separated by a comma (,) or a space (.). A carriage return can also be used to separate instructions and data. The following examples are valid means of issuing the same command:

CS 50,100
CS50,100
CS 50 100
CS
50
100

Commands can be given in a free format with only a few rules governing syntax. The TVM24128 software will lexically analyze the input string and interpret the instruction prior to execution.

Command Options and Attributes

Some commands require attributes that are embedded into the parallel instruction OP code. When using the serial interface, these attributes are presented separately following the two letter serial command code. The example below illustrates this:

FD4,5,7,0,48,data,data,data,data ...
or FD4 5 7 0 48 data data data data ...

Down load to font 4, SizeX = 5, SizeY = 7, Descenders = 0, Offset = 48

Special Binary Data

Some command data is most efficiently sent to the TVM24128 by transmitting binary data directly to the module. This approach is convenient, for instance, when downloading font data. Because binary data can represent any value including special ASCII control characters, a special mode can be entered into to allow sending of this data without conflicts. This mode is entered into by sending an exclamation point "!" prior to any binary data. The module will then receive the next 256 data bytes as binary data without exception. Font data, loaded via this technique, is done so by quantizing the data into packets of 256 bytes. When less than 256 bytes are to be sent, the remainder of the packet is padded with zeros. The example below shows this:

FD4,5,7,0,48!<256 byte packet>!<256 byte packet>

Quoted Strings

ASCII string data such as that given when using the Input String instruction must be contained within quotes. Any printable ASCII character can be placed within the quotes. The following are examples of strings:

| String as given to module | String as printed |
|-------------------------------|-------------------------|
| "This is a string" | This is a string |
| "This \"This\" is quoted" | This "This" is quoted |
| "This \\\"This\\\" is quoted" | This \"This\" is quoted |

Note that a back-slash escapes the quote allowing it to be printed and not delimit the string. A back-slash is printed by sending two consecutive back-slashes.

To print: a ", provide a \"
To print: a \, provide a \\

Returned Data Format

Some commands require data to be returned from the TVM24128 to the host. These data strings are always preceded by a dollar (\$) sign. The following example shows a query to return the length of a button area:

Sent to module: BS5 Ask length of button 5
Returned by module: \$2\n It is 2 cells long.

The following asks for the current XY position:

Sent to module: CS
Returned by module: \$50,100\n

The \n character represents a carriage return. It is always appended at the end of a returned string.

TVM24128

Instruction Errors

Some commands can cause an error condition upon execution. In this case the module will return the pound sign “#” followed by the instruction string that failed. The following example queried the module for the length of a button that had not yet been placed:

| | |
|---------------------|----------|
| Send to module: | BS 5 |
| Returned by module: | #BS\$2\n |

Asked for length of button with code 5. What returned was the error (#) plus the length information which would be two based on buffer information.

Serial data buffer

The TVM24128 contains a 1024 byte serial data buffer. Commands and data which are sent to the module are stored in this buffer prior to being executed. Thus, commands and data can be sent faster than the module can execute each instruction. When using high baud rates and without safeguards, this buffer could eventually overflow causing a loss of data. To prevent buffer overflow, the TVM24128 supports both the RTS/CTS hardware hand shaking protocol and the XON/OFF software hand shaking protocol. The buffer hand shaking is determined through the use of the @H, @L, @X and @R instructions described later.

Default Hand Shaking Protocol

The TVM24128 default serial protocol is RTS/CTS with XON/XOFF software protocol disabled. Typically, the host system software would setup the module operating modes and protocol early in the program. It should be noted however, that regardless of what protocol is selected or enabled, the module will respond to commands and return appropriate data. The hand shaking protocol is used only to manage the contents of the serial data buffer. Some applications may not require hand shaking protocol to be used at all.

Serial Interface Commands

Special commands are provided to allow the host system to control the serial interface of the TVM24128. All of these commands are preceded by the “@” symbol followed by a single character command and optional data.

@K Key press query

Sending the @K command will cause the TVM24128 to return the current keypress status.

| | |
|-----------------|----------------------|
| Send to module: | @K |
| Returned: | @K1 if key press |
| Returned: | @K0 if not key press |

@E Echo String

In some cases, the controlling system must know what instruction the TVM24128 is executing. A method to obtain this information is required since the TVM24128 can buffer as much as 1K bytes of operational data. If a given instruction is inclined to generate an error, the controlling host needs to know when it is executed. The host can then correlate the returned error codes to a particular instruction. The feedback can be generated by following error prone instructions with an @E command. When the host receives the echo string back from the module, the host knows that any error codes received immediately prior where created by the echoed instruction.

Echo capability enables the host to send a block of serial commands as fast as possible and then wait for an appropriate echo before proceeding. The echo string can be of any length but must contain only numbers or letters (alpha numeric) and must not be quoted. The following shows an example of the @E command:

| Sent to module | Received from module |
|----------------|----------------------|
| @E100 | @E100 |
| @EEchoThis | @EEchoThis |

@H @L Set High Threshold, Set Low Threshold

@H and @L are used to set the high and low buffer threshold points. The thresholds are used to determine when to change the CTS (clear to send) signal and when to send the XON/XOFF characters. The default high threshold is set at 800 bytes. The default low threshold is set at 200 bytes. Upon the buffer contents falling below the @L threshold mark, the CTS signal goes high. If XON/OFF is selected, the XON (DC1 or 0x11 hex) character is sent to the host. When the buffer contents rise above the @H threshold mark, the CTS signal goes low. If XON/OFF is selected, the XOFF (DC3 or 0x13 hex) character is sent to the host. Following are examples of the @H and @L instructions:

| | |
|-------|----------------------------------|
| @H850 | Set high threshold to 850 bytes. |
| @H650 | Set high threshold to 650 bytes. |
| @L400 | Set low threshold at 400 bytes. |

@X Enable XON/OFF

Sending @X selects the XON/OFF software hand shaking.

@R Disable XON/OFF

Sending @R disables the XON/OFF software hand shaking.

@S @D Enable/Disable KPS

The TVM24128 can automatically send a special code to the host whenever a key is pressed. This signal, called the KPS signal, is the same as DC2 (0x12 hex). If @S is sent to the module, it enables the module to automatically send the KPS signal when a key is pressed. This allows the host system to interrupt what it is doing and service the keyboard without the host continuously polling the module using the @K command.

The @D command disables the KPS feature.

RS232 Interface Description

The RS232 hardware connections are made via a 10 pin shrouded header (JA5). The pins are ordered as is a DCE (modem). The TVM24128 requires a straight through cable connection often referred to as a "NULL MODEM".

Serial Data Protocol

All serial data communication uses 8 bit, NO parity and 1 stop bit protocol.

Signal Names


The table below and following figure show the RS232 connector pin designations:

| Pin # | Function | Description | Type |
|-------|----------|-------------------|--------|
| 1 | Ground | Ground connection | |
| 2 | Ground | Ground Connection | |
| 3 | TD | Transmit Data | Output |
| 4 | RTS | Request to send | Input |
| 5 | RD | Receive Data | Input |
| 6 | CTS | Clear to send | Output |
| 7 | N/C | No connection | |
| 8 | Ground | Ground Connection | |
| 9 | Ground | Ground Connection | |
| 10 | N/C | No connection | |

JA5 RS232 Port Connections

TVM24128

The connector pins are ordered in such a way that a simple adapter can be made converting the 10 pin connector to a 9 pin D-SUB connector typically used on compatible PC's. A wiring diagram for the cable follows:



10 PIN Header to 9 pin D-SUB PC RS232 Cable

Signal Description

Following is a description of the RS232 signals.

- TD** This is the TVM24128 transmitter output.
- RD** Receives data from the host processor.
- RTS** The signal provided by the host system to tell the module it is ready to send data. The module will then raise the CTS signal if the buffer is below the full threshold. As long as RTS stays low, the TVM24128 will not raise the CTS signal. Tying this line high (+5 V) will permanently enable the CTS signal to indicate the current buffer status.
- CTS** This signal provided by the TVM24128 tells the host system that it is ready to receive data. If the TVM24128 buffer is below the high threshold when RTS goes high, CTS will go high. Upon the buffer filling above the high threshold, CTS will go low and stay low until the buffer contents fall below the low threshold. If RTS is taken low and high again, the module will re-evaluate the buffer status and raise the CTS signal if the buffer is below the high threshold. CTS can not go high unless RTS is also high.

If software hand shaking is employed, both CTS and RTS can be left disconnected.

Baud rate selection

The TVM24128 can operate at any of 8 baud rates. The baud rate is selected by the module at the time reset occurs by reading the baud rate jumpers JO1, JO2 and JO3. A shorting clip between the center pin and pin 3 programs the baud jumper to a logic one. The table below shows the available baud rates and associated jumper combinations:

| | Baud Rate | JO1 | JO2 | JO3 |
|--|-----------|-----|-----|-----|
| The baud rate is only set during reset. | 300 | 0 | 0 | 0 |
| | 600 | 0 | 0 | 1 |
| | 1200 | 0 | 1 | 0 |
| | 2400 | 0 | 1 | 1 |
| | 4800 | 1 | 0 | 0 |
| | 9600 | 1 | 0 | 1 |
| | 19200 | 1 | 1 | 0 |
| | 38400 | 1 | 1 | 1 |

Baud Rate Jumper Selection

Mixed Mode Operation

The TVM24128 has the unique ability to operate in a combined parallel and serial mode. Commands and data from both the serial and parallel interface can be received as long as commands do not overlap due to simultaneous transmission by the host or hosts. If the operational data overlaps, the module will mix and match serial and parallel commands and data and execute a composite of both. This will result in some unpredictable behavior.

Instruction Set Summary

| | Parallel Instruction | Serial Instruction |
|---------------------------|---|--|
| Font Selection | | |
| Select Font | 00000xxx | FS{xxx} |
| Down Load Font | 00001xxx,SizeX,SizeY,Offset,Descenders String... | FD{xxx},{SizeX},{SizeY},{Offset},{Descenders}, !<256 byte packet>!<256 byte packet> ... |
| Set Font Attributes | 000110ab | FA{ab} |
| Select Font Gray Palet | 1011AABB | FG{AABB} |
| Set Font Plane | 0001001x | FP{x} |
| Cursor Positioning | | |
| SetXY | 00100000,Xpos,Ypos | CS{XPos},{YPos} |
| ReadXY | 00100001,[Xpos],[Ypos] | CG[\${XPos},{YPos}\n] |
| Cursor Up | 00100010 | CU |
| Cursor Down | 00100011 | CD |
| Cursor Left | 00100100 | CL |
| Cursor Right | 00100101 | CR |
| SetX | 00100110,Xpos | CX{XPos} |
| SetY | 00100111,Ypos | CY{YPos} |
| Set Cursor Attributes | 00010abc | CA{abc} |
| Text Configuration | | |
| Set Text Window | 00101000,AX,AY,BX,BY | TW{AX},{AY},{BX},{BY} |
| Set Pitch | 00101010,Pitch | TP{Pitch} |
| Set Height | 00101011,Height | TH{Height} |
| Text Input | | |
| Input String | 00101100,String... | IS"Quoted String" |
| Graphics Input | | |
| Draw Box | 0100TTTT,AX,AY,BX,BY | GX{TTTT},{AX},{AY},{BX},{BY} |
| Draw Block | 011000TT,AX,AY,BX,BY | GB{TT},{AX},{AY},{BX},{BY} |
| Draw Horiz | 011001TT,Xpos,Ypos,Length | GH{TT},{XPos},{YPos},{Length} |
| Draw Vert | 011010TT,Xpos,Ypos,Length | GV{TT},{XPos},{YPos},{Length} |
| Draw Vector | 011011TT,AX,AY,BX,BX | GC{TT},{AX},{AY},{BX},{BY} |
| Set Pixel | 011100TT,Xpos,Ypos | GI{TT},{XPos},{YPos} |
| Set Gray Palet | 1100AABB | GG{AABB} |
| Set Graphics Plane | 0111100x | GP{x} |
| Button Input | | |
| Place Button | 00110000,KeyCode,0RRRCCCC | BC,{KeyCode},{RRRCCCC} |
| Load Button Buffer | 00110001,String... | BL"Quoted String" |
| Get Button Size | 00110010,KeyCode,[RData] | BS[\${Size}\n] |
| Place Phantom Butt. | 00110011,KeyCode,0RRRCCCC,BLength | BH,{KeyCode},{RRRCCCC},{BLength} |
| Delete Button | 00110100,KeyCode | BD{KeyCode} |
| Delete All Buttons | 00110101 | BE |
| Read KeyCode | 00110110,[RData] | BK[\${KeyCode}\n] |
| Set Button Attributes | 00111abc | BA{abc} |
| Set Button Gray Palet | 1101AABB | BG{AABB} |
| Set Button Plane | 1110000x | GP{x} |

TVM24128

Instruction Set Continued

Display Control

| | Parallel Instruction | Serial Instruction |
|--------------------|-------------------------------|----------------------------------|
| Blank Display | 10000000 | DB |
| Clear Display | 10000111 | DC |
| Dump Display RAM | 10000100,[RData...] | Not Available |
| Load Display RAM | 10000101,String... | Not Available |
| Move Block Vert | 01110100,AX,AY,BX,BY,Distance | DV{AX},{AY},{BX},{BY},{Distance} |
| Move Block Horiz | 01110101,AX,AY,BX,BY,Distance | DH{AX},{AY},{BX},{BY},{Distance} |
| Load Gray Dither | 10000010,GD1,GD2 | DD{GD1},{GD2} |
| Reverse Video Mode | 1000110R | DR{R} |

System Instructions

| | | |
|-----------------|-----------------------------------|--|
| Soft Reset | 11111110 | SR |
| Set Contrast | 11110011,Data | SC{Data} |
| Set EL | 1111010a | SE{a} |
| NOP | 11111111 | SN |
| Set Beeper | 1111000a | SB{a} |
| Read Key Matrix | 11110010,[RData (12 bytes total)] | SK [{byte 1},{byte 2}, ..., {byte 12}\n] |
| Write Aux Port | 11111000,0000xxxx | SW{xxxx} |
| Read Aux Port | 11110111[AuxData] | SA [{Aux Data}\n] |

Serial Interface Instructions

The following instructions are used in serial interface applications.

| Name | Instruction | Description |
|-------------------------|----------------------|--|
| Query Keypress | @K | Returns @K1 if Keypress is set, @K0 if not. |
| String Echo | @E{alpha num string} | Echoes the alpha numeric string sent. |
| Set Buffer High Thresh. | @H{number} | Sets the receive buffer high threshold. |
| Set Buffer Low Thresh. | @L{number} | Sets the receive buffer Low threshold. |
| Enable XON/XOFF | @X | Turns on the XON/XOFF hand-shaking protocol. |
| Disable XON/XOFF | @R | Turns off the XON/XOFF. |
| Enable KPS | @S | Enable KPS when a key is pressed. KPS is DC2 (0x12). |
| Disable KPS | @D | Disables KPS. |

Power Supply Considerations

When using the TMV24128 with the parallel interface, power and ground is generally supplied via the power pins of the connector JF1. The RS232 power connector can optionally be used to supply power and ground if desired.

The serial interface requires that power and ground be supplied via the RS232 power connector if the parallel cable is not being used simultaneously.

The metal bezel is connected to ground via a top-side trace located near the RS232 power connector. The trace is clearly marked in the metal layer itself. If desired, the bezel can be connected to a separate ground by cutting the marked trace and connecting the pad closest to the edge of the board to an external ground.

If an external EL power supply is desired, the shunt across pins 2 and 3 of header JO6 can be removed and power can be supplied via pin 2 (Positive) and pin 1 (Ground) of the same header.

TVM24128

DC Electrical Characteristics:

$V_{CC} = 5.0V \pm 5\%$ unless otherwise specified.
 $T_A = 25\text{ }^{\circ}\text{C}$ Unless otherwise specified.

| Parameter | Min | Typ | Max | Units | Conditions |
|---|----------------------|------------|--------------------|-------------------|--|
| Power Supply Voltage Supply Current, Back-light OFF Back-light ON | 4.75 | 175 450 | 5.25 210 500 | Volts mA mA | $V_{CC} = 5.0\text{ Volts}$ |
| V_{IL} Input Low Voltage D7-D0,DA1,DA0,DWR/,DRD/,DEN/,Aux inputs | - 0.5 | | 0.8 | Volts | |
| V_{IH} Input Hi Voltage D7-D0,DA1,DA0,DWR/,DRD/,DEN/, Aux inputs | 2.0 | | V_{CC} | Volts | |
| V_{OL} Output Low Voltage D7-D0,DBUSY,DREADY/,ERROR,KEYPRESS | | | .4 | Volts | $I_{OL} = 2.5\text{ mA}$ |
| V_{OH} Output Hi Voltage D7-D0,DBUSY,DREADY/,ERROR,KEYPRESS | 3.0 $V_{CC} - .4$ | | | Volts Volts | $I_{OH} = -2.5\text{ mA}$ $I_{OH} = -100\text{ uA}$ |
| I_{OZ} Output Floating Leakage D0-D7 | ± 50 | | ± 300 | μA | $V_{IN} = V_{CC}\text{ or }0\text{ Volts}$ |
| I_{OL} Output Current Auxiliary Outputs | 50 | | | mA | $V_{OH} = .5\text{ Volts}$ |
| $\overline{\text{RESET}}$ (Active Low) $\overline{\text{RESET}}$ (Inactive Hi) | 4.5 | | .5 | Volts Volts | 22K Pull Up |
| External EL Supply Voltage External EL Supply Current | 3.0 | | 5.5 200 | Volts mA | |
| RS232 Port Specifications | | | | | |
| Input Voltage Operating Range | - 30 | | +30 | Volts | |
| Input Threshold Low | 0.8 | | 1.2 | Volts | |
| Input Threshold High | | 1.7 | 2.4 | Volts | |
| Input Hysteresis | 0.2 | 0.5 | 1.0 | Volts | |
| Input Resistance | 3 | 5 | 7 | kOhms | |
| Output Voltage Low | | - 9.0 | - 5.0 | Volts | $I_{OUT} = 3.2\text{ mA}$ |
| Output Voltage High | 5.0 | 9.0 | | Volts | $I_{OUT} = 1.0\text{ mA}$ |
| Instantaneous Slew Rate | | | 30 | V/uS | $C_L = 10\text{ pF}$, $R_L = 3\text{-}7\text{ kOhms}$ |
| Transition Region Slew Rate | | 3 | | V/uS | $C_L = 2500\text{ pF}$, $R_L = 3\text{ kOhms}$ |
| Output Resistance | 300 | | | Ohms | $V_{OUT} = \pm 2\text{ Volts}$ |
| Output Short Circuit Current | | ± 10 | | mA | |
| | | | | | |


TVM24128

AC Electrical Characteristics


$V_{CC} = 5.0V \pm 5\%$ unless otherwise specified
 $T_A = 25^\circ C$ Unless otherwise specified

| Symbol | Parameter | Min | Max | Units |
|-----------|----------------------------|-----|-----|-------|
| T_{wp} | Write Pulse Width | 100 | | nS |
| T_{asw} | Address Setup Write | 5 | | nS |
| T_{ahw} | Address Hold Write | 50 | | nS |
| T_{ws} | Write Data Setup | 20 | | nS |
| T_{wh} | Write Data Hold | 60 | | nS |
| T_{ibf} | Write to IBF High | | 100 | nS |
| T_{rp} | Read Pulse Width | 100 | | nS |
| T_{asr} | Address Setup Read | 5 | | nS |
| T_{ahr} | Address Hold Read | 0 | | nS |
| T_{ra} | Read Data Access | | 100 | nS |
| T_{rh} | Read End to Data Tri-state | | 50 | nS |
| T_{obf} | Read to OBF High | | 100 | nS |

Timing Waveforms




Write Cycle Timing




Read Cycle Timing

Parallel Interface Examples



6801 Parallel Interface Example




8085 Parallel Interface Example

Additional Information


Applications information plus expanded information on the instruction set can be found in the TVM24128 Designer's Manual. If you need additional technical information, please contact C Sys Labs.

TVM24128

Mechanical Outlines:



Sound Transducer



C Sys Labs, Inc. reserves the right to make changes without notice to any products herein to improve function, reliability or design. C Sys Labs, Inc. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights nor the rights of others. C Sys Labs and Touch Vision are trademarks of C Sys Labs, Inc.

© 2000 C Sys Labs, Inc.

C Sys Labs, Inc. 1430 Koll Circle Suite 103 San Jose, CA 95112 Telephone (408) 453-5380 FAX (408) 453-5382